



Cyclone™ On Demand Cylinder Printer



Product Specifications

PRINT RESOLUTION: 300 dpi x 600 dpi

PRINT SPEED: Up to 1 in/sec. (2.5 cm/sec.)

OPERATING SYSTEMS: Windows XP, Vista, & Windows 7

PRINTER DRIVER: ImPress Systems Custom Driver

SOFTWARE COMPATIBILITY: Most Windows applications

I/O INTERFACE: Universal Serial Bus (USB) & Serial

POWER REQUIREMENTS: 100 - 240 VAC; 50/60 Hz

EXTERNAL AIR SOURCE: Clean, dry house air Inlet pressure 90 - 110 psi

DIMENSIONS: 13"(33 cm) W x 15"(38 cm) H x 14"(36 cm) D

WEIGHT: 29 lbs. (13 kg)

PRINT SUBSTRATES: Cylinders (smooth plastic and coated surfaces with a linear taper no greater than 1 degree or 18 mil/in)*

CYLINDER DIAMETER: .30"(.8 cm) to .5"(1.3 cm); up to 1"(2.5 cm) with tooling

PRINT WIDTH: Maximum 2.13" (5.4 cm)

PRINT LENGTH: Variable based on the circumference of cylinder

APPLICATIONS: Pens, pencils, markers, glow products, syringes, vials & tubes, as well as industrial applications

7C Stuart Road, Chelmsford, MA 01824 USA

Phone: (978) 441 - 2022 Fax: (978) 441 - 2032

www.impresssystems.com

** Requires 2.5" (6.4 cm) of space on barrel that is free of any obstructions (such as clips, grips, etc.) that would interfere with the rotation of the barrel on the rollers.*